

TECHNICAL SPECIFICATION



MARTCARE® M Series

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M22 - FFP2V / BEH120-002-A00



DESCRIPTION

The Martcare® range offers a cost-effective solution, with a straightforward selection of easy-to-use PPE, subject to the rigorous batch testing and conformity procedures applicable to the entire JSP PPE range.

OPTIONS

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M22 - FFP2V (BEH120-002-A00)

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M32 - FFP3V (BEH130-002-A00)

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M21 - FFP2 (BEG120-002-B00)

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M31 - FFP3 (BEG130-002-B00)

SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 Apr 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate, Valved)

Usage
NR (Non-Reusable)



Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
8%

UK Assigned Protection Factor
10



Exhalation Valve
Yes - Polystyrene exhalation valve with rubber diaphragm

Mask Material
Polypropylene



Product Weight
16g (Approx)



Filter Type
P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging
Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency
94% For FFP2 Rated

Nominal Protection Factor
12


Mask Design
Moulded



Nose Bridge
Moulded in mask


Filter Shelf Life
5 Years

FEATURES



Inner Foam Nose Bridge

Foam padding around the nose area of the mask provides comfort and a firmer fit.



Exhalation valve

Low resistance exhalation valve for easy breathing.



Metal Free Straps

Mask straps ultrasonically welded ensuring no metal parts in contact with the face.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace

Agricultural

Airports

Construction and Infrastructure

Facilities Management

Food and Drink Manufacturing

Forestry & Landscaping

Hospitals, Healthcare & Pharmaceuticals

Law Enforcement

Manufacturing

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

Transportation, Warehousing & Logistics


Utilities Contractors

RANGE



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-disposable-dust-masks-martcare-m-series-m22.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 Apr 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.

