

ASKYTEC CH102

DURABLE, OIL-RESISTANT, TRIPLE-DIPPED PVC GLOVE WITH EXTENDED CUFF

SKYTEC CH102 features a soft comfortable cotton lining and a rough textured PVC coating that ensures grip in contact with oils and chemicals. Extended cuff to protect the entire arm.

FEATURES

- A flexible, soft glove that absorbs perspiration, for ultra comfortable extended wear and with good mechanical resistance
- > Seals and protects the hand against chemicals while remaining flexible
- ➤ Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- > Excellent abrasion resistance (EN388 Level 4)
- > Surface provides tactile feel and better grip
- > Designed for easy movement and continuous wear
- > No irritation by seams in contact with the skin
- > Arm entirely protected with the extended cuff
- > Thickness: 1.3mm









SUITABLE FOR

Typical Industries

- Agriculture
- Automotive
- Chemical
- Construction
- Petrochemical
- Public Utilities

Suitable Applications

- Commercial Fishing
- Chemical Handling
- Decontamination Work
- Dipping
- Drain/Sewer Cleaning
- Engine Servicing

CAT III EN 388:2016 + A1:2018 A1:2018 A1:21X See overleaf for explanation





△SKYTEC CH102

PRODUCTION INFORMATION

MATERIALS	LINER:	Cotton
	COATING:	PVC
COLOUR	Dark blue	
LENGTH (mm)	600 (Size dependant)	
CUFF STYLE	Gauntlet	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00069DD SKG00069DF SKG00069DH SKG00069DJ SKG00069DL	12 pairs per bag 48 pairs per case


RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxide
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
I	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
Α	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical

MICRO VIRUS =

3

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604: 2004 (method B)

GLOBUS

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)1618774747 F: +44 (0)1618774746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +97148829962 F: +97148829963

offerd Park Manchaster M171SH LINITED KINGD

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-CH102-1023_1

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com