

HONEYWELL NIT'LITE® MAXI BOOT EVO

I Shoes that withstand extreme temperatures

With the NIT'LITE® range, Honeywell teams have created the nitrile rubber shoe sole with an expanded cellular structure, for greater lightness and comfort. The nitrile sole offers excellent resistance to extreme temperatures (up to 300°C), to fuel and hydrolysis. The comfort is unmatched thanks to the lightness and elasticity offered by NIT'LITE®.



MAXI BOOT EVO S3 HRO SRC

- Mid-cut style
- Black pigmented leather upper
- Padded ankle collar for ankle protection
- Resistant to fluid spillages
- Outsole resistance up to 300°C
- S3 marking:
 - Toecap resistant to an impact of 200 Joules and crushing of 15 kN
 - Closed heel area
 - Antistatic properties
 - Heel energy absorption
 - Resistance to fuel oil
 - Water penetration and absorption
 - Anti-puncture resistance
 - Cleated outsole
- HRO marking: resistance to hot contact
- EN ISO 20345:2011 S3 HRO SRC

Excellent abrasion
resistance

Resistance to oils,
fuel and common
chemicals

Resistance to extreme
temperatures: up to
300°C

Good resistance to hot
and humid conditions

Lightness and
flexibility thanks to
a unique expanded
cellular structure

SRC slip resistance
according to the latest
EN ISO 20345:2011
standard

Honeywell

THE FEATURES THAT MAKE THE DIFFERENCE

TECHNICAL SPECIFICATIONS AND STANDARDS:

- European Regulation: (EU) 2016/425*
- Standard: EN ISO 20345:2011**
- Quality assurance: ISO 9001 Version 2015***
- Marking: S3 HRO SRC
- Average weight for 1 shoe 42 size: 705 g

*) <https://ojsa.europa.eu/en/safety-and-health-legislation>

**) <https://www.iso.org/home.html>

***) <https://www.dnv.com>

OUTSOLE SLIP RESISTANCE PERFORMANCE

MARKING	SURFACE	LUBRICANT	FRICTION FACTOR: FLAT
SRA	Ceramic plates	Sodium lauryl sulfate	0.42 (minimum requirement 0.32)
SRB	Steel	Glycerol	0.18 (mimimum standard 0.18)
SRC	Meets requirements of the above 2 tests (SRA plus SRB)		

ORDERING INFORMATION

DESCRIPTION	REF.	SIZE
Maxi Boot Evo S3 HRO SRC	62 458 96	38-47

For More Information

www.honeywellsafety.com

HONEYWELL SAFETY PRODUCTS UNITED KINGDOM

Honeywell Safety Products UK LTD
Honeywell House, Skimped Hill Lane,
Bracknell, Berkshire RG12 1EB
United Kingdom
Phone: +44 (0) 1256 274938
Email: info-uk.hsp@honeywell.com

HONEYWELL SAFETY PRODUCTS NORDICS

Honeywell Safety Products Nordic AB
Strandbadsvägen 15
SE-252 29 Helsingborg – Sverige
Phone: +46 (0) 424480433
Email: info-nordic.hsp@honeywell.com

HONEYWELL SAFETY PRODUCTS BENELUX

Honeywell Safety Products Benelux BV
Lange Amerikaweg 55
7332 BP Apeldoorn, Nederland
Tel: +31 (0) 20 5656 988
Email: info-benelux.hsp@honeywell.com

FOOTWEAR | HONEYWELL NIT'LITE® | 05/2021
© 2021 Honeywell International Inc.

Honeywell